

PTF2-L Spec-sheet



LoRaWAN® Operated Low Power Flush Type Pressure Transmitter for Liquid and Gas Media

- Compatible with all LoRaWAN® frequencies
- Wide range of industrial applications
- High accuracy
- Designed to meet outdoor applications
- Long-term durable performance in harsh environment
- Ultra-low power
- Suitable for liquids and gases compatible with SS



TECHNICAL SPECIFICATION

Sensor

• Range	Selectable between 0~0.5 to 0~100	bar
• Accuracy	±0.25 (typ.) <small>(combined linearity, hysteresis, repeatability)</small>	%Span
• Resolution	±0.01	%Span
• Pressure Reference	Vented Gauge, Sealed Gauge, Absolute	
• Temperature Coefficient of Zero	≤±0.02	%FS/°C
• Temperature Coefficient of Span	≤±0.02	%FS/°C
• Long Term Stability (1 year)	≤ 0.2	%Span
• Pressure Overload	300 (range <1bar); 150 (higher range)	%FS
• Pressure Cycles (Zero to Full Scale)	10+	Million
• Compensated Temperature	-10 ~ +70	°C

Power

• Power Supply	Built-in Replaceable Lithium Battery, External Power (option)	
• Rated Voltage	3.6	V
• Battery Lifetime	Typ. 50,000+ readings / 20,000+ transmission <small>(connected to ellenex platform and standard network quality)</small>	

Physical

• Materials	O-ring: Viton, Body: SS304, Diaphragm: SS316, Oil: Silicon / Olive, Enclosure: ASA/POM	
• Process Connection	G1/2 Male (or others on request)	
• Weight	550	g

physical

• Protection Rate	IP66, UV Protected	
-------------------	--------------------	--

Communication

• LoRaWAN® Version, Class	1.0.2revB, Class A (Class C on request)	
• LoRaWAN® Frequency Zone	AS923, EU868, US902-928, AU915-928 <small>(other zones available on request)</small>	
• LoRaWAN® Activation Type	OTA (default), ABP	
• Sampling Type	Periodic (default), Event triggered	
• Sampling Period	Configurable via downlink (default 4 hours)	
• Transmission Type	Per sample (default), Event triggered, Conditional	

PTF2-L Spec-sheet

• Parameter Configuration	Over-the-air via LoRaWAN® downlinks Locally via wireless connectivity
• Firmware Update	Locally via Wireless Connectivity, Over The Air

NETWORK CONNECTION AND VISUALISATION

Network Integration

- Pre-configured to ellenex LNS or configurable to all main network servers (AWS, Netmore, ChirpStack, Helium, Kerlink, Kona Tectelic, Loriot, machine-Q, Orange, Orbiwise, Proximus, Swisscom, TATA, The Things Network (TTN), TTI and any other network)

Visualization And Data Management

- Ellenex white label microservice platform, and Integratable to all main IIoT platforms directly or through the api (AWS, Azure, PTC ThingWorx, Bosch IoT, Cisco Jasper & Kinetic, Sierra Numerex, MathWorks, ThingSpeak, GE Digital Predix, LandisGyr, Siemens MindSphere, Cumulocity, myDevices, Ubidots, TagoIO, HPE IoT and any other major IoT platform).

Ellenex Platform Main Features

- Encrypted ultra-low power communication protocol
- Advanced device inventory
- Integration APIs for enterprise systems
- Multi-tenant role-based access control
- Data export and import
- White-label platform for enterprise runs on private account
- Variable alarm setting for high and low thresholds and multi-channel alerting
- Sampling and transmission interval configuration
- Transmission condition configuration
- Other configurations and customization available on request



Encrypted & ultra-low power



Integratable



Dynamic alerting



Multi-tenant



Scalable



Composable & API first

INDUSTRIES



Food & Beverage



Agriculture & Farming



Transport & Logistics



Water & Environment







Marine & Oceanography



Oil & Gas

PTF2-L Spec-sheet

MODEL GUIDE

Model	Options:	
<p>C Model:</p> 	 <p>C8: IP68 sealed gauge sensor, compact, POM enclosure</p>	 <p>C5: IP65 vented gauge sensor, compact, POM enclosure with on/off switch</p>
<p>T2 Model:</p> 	 <p>C5 with 2inch Tri-clamp: IP65 vented gauge sensor, compact, POM enclosure with on/off switch</p>	
<p>E Model:</p> 	 <p>E5: IP65 sensor (vented gauge), wired, IP66 ASA enclosure and on/off switch</p>	

APPLICATIONS

- Food Liquid Storage Level Monitoring
- Beverage Machineries
- Water Pipeline Pressure Monitoring
- Pressurized System Monitoring
- Chiller and Cooling System Monitoring
- Pharmaceutical applications
- Agricultural equipment
- Hydrostatic level monitoring
- Spraying System Monitoring
- Air Compressor Monitoring

PTF2-L Spec-sheet



ORDERING CODE

PTF2-L										
LoRaWAN Frequency Zone										
AS (AS923)		AUx (AU915-928) (Sub Band x)			EU (EU868)		USx (US902-928) (Sub Band x)			
LoRaWAN Activation										
A (Over the air activation - OTAA)					P (Activation By Personalization - ABP)					
Pressure Range										
0.5, 1, 2, 5, 10, 20, 50, 100bar (or any other positive or negative ranges)										
Pressure Reference										
V (Vented Gauge)			S (Sealed Gauge)			A (Absolute)				
Process Port										
G1/2 (1/2" BSPP Male)			NPT1/2 (1/2" NPT Male)			T2 (2" Tri-clamp)				
Thick Film G1/2 (1/2" BSPP Male)						Other options on request				
Enclosure										
C5 : Cylindrical				C8 : Cylindrical - IP68 rated						
E5 : Rectangular - IP66 enclosure with sensor extended using a 3m cable (or other options on request)										
Device Activation										
S : With On/Off Switch						X : No Switch (Always On)				
Antenna Option										
E : External						I : Internal				
Options										
(On request) ¹										
PTF2-L	AS	A	1bar	V	G1/2	C5	S	E		

Sample Product Code:

- **PTF2-L-AS-A-1bar-V-G1/2-C5-S-E**

LoRaWAN® flush type pressure sensor, frequency of AS923, Over The Air Activated, pressure range of 1bar vented, process connection of G1/2 with cylindrical housing (compact and IP65 rated), activated by on-off switch and equipped with external antenna.

1) Product Options:

- **EPB**: sensor with external power supply connector for 12V supply with internal battery backup (only for E type enclosure, adaptor is not included)
- **HG**: high-gain external antenna
- **HCB**: high-capacity battery (only for E type enclosure)

