



Remote Wastewater Tank Level Monitoring

Effectively monitoring wastewater tank levels in remote areas is critical to maintaining efficient operations, reducing costs, and minimizing environmental impact.

CHALLENGE

In remote locations or areas with limited accessibility, traditional wastewater tank level monitoring systems can be challenging to implement and maintain. The lack of continuous data collection and manual inspections can result in inefficient operations, increased costs, and potential environmental hazards.

SOLUTION

Ellenex's battery-operated Submersible Level Sensor with corrosion resistance, leveraging NB-IoT technology, provides an ideal solution for remote wastewater tank level monitoring. The specific IoT sensor used in this case is Ellenex's Submersible Level Sensor, which is ruggedized and IP65 rated, making it perfect for harsh industrial applications.

Benefits of using this approach:

- Near real-time monitoring: With data transmitted every few hours, operators can make informed decisions and respond quickly to changing conditions.
- Corrosion resistance: Ellenex sensors are built with corrosion-resistant materials to withstand harsh wastewater environments.

Remote Wastewater Tank Level Monitoring



- Battery-operated: No external power source is required, making the sensor suitable for remote locations.
- Ruggedized and IP65 rated: Designed for harsh industrial applications, ensuring reliable performance in challenging environments.
- Low maintenance: The NB-IoT technology allows for seamless communication, reducing the need for manual inspections and maintenance.
- Cost reduction: The automated monitoring system reduces labor costs associated with manual inspections and potential damage due to inefficient monitoring.
- Environmental protection: Timely detection of wastewater overflow or leakage prevents environmental contamination and complies with regulations.

This solution helps address the challenge of remote wastewater tank level monitoring by providing near real-time data, reducing maintenance requirements, and ensuring efficient operations that minimize environmental impact.













Battery Operated

Ruggedised Design

Easy Install

Pre-Configured

Secure

cure

TECHNOLOGY

Ellenex employs cutting-edge communication technology by utilizing the LTE Cat M1 protocol, which operates on 4G and 5G cellular networks, making it suitable for mobile and stationary monitoring applications. However, its remarkably low power consumption and superior penetration rate, specifically designed for industrial solutions, sets it apart. Narrowband Internet of Things (NBloT) and LTE Cat M1 are advanced communication technologies that offer significant advantages for monitoring applications. These technologies provide efficient and reliable connectivity for IoT devices, allowing for seamless communication between our sensor and remote monitoring systems. NB-IoT and LTE Cat M1 are known for their low power consumption, enabling



Remote Wastewater Tank Level Monitoring



prolonged battery life for the devices, which is crucial for remote or hard-to-reach areas. Moreover, these technologies offer excellent penetration capabilities, allowing for reliable communication even in challenging environments, such as underground or remote locations where devices are often deployed. NB-IoT and LTE Cat M1 also provide secure and scalable connectivity, enabling robust and cost-effective solutions for monitoring applications in various industrial sectors, including agriculture, utilities, logistics, and more.



SENSOR TECHNICAL SPECIFICATIONS

٠	Range	3m (or other ranges upto 200m)	m
•	Accuracy (combined linearity, hysteresis, repeatability)	±0.25 (typ.)	%Span
٠	Resolution	±0.01	%Span
•	Temperature Coefficient of Zero	≤±0.03	%FS/°C
•	Temperature Coefficient of Span	≤±0.03	%FS/°C
٠	Long Term Stability (1 year)	≤ 0.2	%Span
•	Overload Protection	150	%FS
•	Load Cycles (Zero to Full Scale)	10+	Million
٠	Storage / Operation Temperature	-20 ~ +85	°C
•	Compensated Temperature	0 ~ +60	°C
•	Power Supply	Built-in Replaceable Lithium Battery	
•	Rated Voltage	3.6	V
٠	Battery Lifetime	10,000+ transmissions	
•	Materials	Body: Hastelloy or PVDF, Diaphragm: Hastelloy or Ceramic (Al2O3), Enclosure: POM, O-ring: FKM/ FFKM	
•	Weight	~1200 (for 5m range)	g
٠	Protection Rate	IP66, UV Protected enclosure and IP68 sensor head	
•	SIM Card Type	4FF Nano-SIM, from any Network Provider	
•	Firmware Update	Over The Air, Locally via Wireless Connectivity	
•	Sampling Period	Configurable via downlink (default 4 hours)	
٠	Communication Bands	B1/B2/B3/B4/B5/B8/B12/B13/B18/B19/B20/B26/B28 and B39	
٠	Antenna	Internal (Default)/ External (customised options available)	

Remote Wastewater Tank Level Monitoring



PLATFORM FEATURES

Ellenex's software platform is a comprehensive and user-friendly solution specifically designed for diesel delivery management. The platform offers a wide range of features tailored for diesel delivery operations, including real-time data visualization, customizable alerts and notifications, historical data analysis, and predictive analytics. It provides users with a holistic view of their diesel delivery assets, allowing them to make data-driven decisions for optimal fuel management. The platform is accessible via web browsers and mobile devices, providing convenient remote access to critical information anytime, anywhere. Ellenex's software platform is designed with a user-centric approach, offering intuitive navigation and a user-friendly interface for easy setup and configuration. With its advanced features and ease of use, Ellenex's software platform empowers users to effectively monitor and manage their diesel delivery operations in remote areas, ensuring efficient and sustainable fuel resource management.

- Encrypted ultra-low power communication protocol
- Advanced device inventory
- Integration APIs for enterprise systems
- Multi-tenant role-based access control
- Data export and import
- White-label platform for enterprise runs on private account
- · Variable alarm setting for high and low thresholds and multi-channel alerting
- Sampling and transmission interval configuration
- Transmission condition configuration
- Other configurations and customisation available on request




Remote Wastewater Tank Level Monitoring





Image: Second second


Single shot data visualisation of devices




Asset location indication and complex formula









Remote Wastewater Tank Level Monitoring





INTEGRATION OPTIONS

Ellenex's solution sets itself apart with its pre-configured and plug-and-play design, eliminating the complexities of configuration, programming, and connection to the platform. This unique approach ensures that users can start monitoring their diesel tanks quickly and easily without any technical hassles. Additionally, Ellenex offers seamless integratability at both the network and platform levels, allowing for easy integration with any network or visualization/analysis platform. This competitive advantage makes Ellenex's solution highly adaptable and compatible with existing systems, providing users with flexibility and convenience in managing their diesel resources effectively.

ORDERING PROCESS

Ellenex offers simple and easy way to order the solution from any location on earth with narrow band cellular coverage. Please visit our sales portal (www.ellenex.shop) or contact us to discuss your application. This is the first step to experience a reliable IoT solution at scale.

Remote Wastewater Tank Level Monitoring









Learn more about our Software Platform



View the Included Sensor Datasheet



Browse our other solutions

All details are subject to change without prior notice © All Rights Reserved for Ellenex

Ver. 1.3-05/23

ellenex

Integrated IoT Solutions

Email:sales@ellenex.comWeb:www.ellenex.comPlatform:ellenex.netSales Portal:www.ellenex.shop